

# Protectorshell

**Protectorshell Articulated Pipe** has been developed to provide shallow water abrasion and impact protection for submarine cables.

**Protectorshell** is unique in that it clips together, avoiding the nuts and bolts of traditional articulated pipe. This clip together feature allows quick real time application during laying and a much simplified diver installation onto pre-laid cables.

The **Protectorshell** system comprises two different cast segments which are identified as uppers and lowers. Each successive pair of segments clips over and retains the end of the preceding pair.

A wide range of adaptors and attachments are available for use with **Protectorshell** Articulated Pipe. These adaptors and attachments allow the reversal of application direction and interfacing with other cable protection measures such as directionally drilled pipes, pipe flanges and concrete abutments.



## PS200/440/10

### Specifications

Segment Length - Overall	505mm
Effective Installed Length/segment pair	440mm
Minimum Internal Diameter	220mm - for cables up to 180mm diameter
Maximum External Diameter	340mm
Wall Thickness	10mm
Material	Ductile Iron to ISO 1083
Tensile Strength / Elongation	400MPa / 15% elongation
Impact Resistance	>7.5kJ
Minimum Bend Diameter	6.5m
Weight per Segment	31kg
Weight per installed metre (air)	70kg
Weight per installed metre (water)	61kg
Fasteners	M16x70 Bolt and M16 Nyloc Nut – Material: Stainless Steel G316/A4 Recommended usage: 1 pair per 10 metres of installed pipe

#### Protectorshell SL

C Regata Cutty Sark No 21 4 IZ 15002 La Coruña, Spain  
T: +34 8 8124 1115 F: +34 8 8192 4978

[www.protectorshell.com](http://www.protectorshell.com)

#### MS Diversified Services Pty Limited

PO Box 150 Maroubra NSW 2035 Australia  
1135 Anzac Parade, Matraville, NSW 2036 Australia  
T: +61 2 9694 1004 F: +61 2 9314 3526

